



Seated multi-directional forklift(narrow body)

Manufacturer		NEOlift
Model		NRQZ25
Power Type		Battery
Operation Type		Seated
Rated Capacity	kg	2500
Load Center	mm	600
Distance from center of front wheel to fork face	mm	492
Front Overhand	mm	248
Wheelbase	mm	1700
Service Weight(incl.battery)	kg	5150
Wheel Types		PU
Load Wheel	mm	φ343×130
Drive wheel	mm	φ400×160
Number of wheels,,front/rear(x=drive wheel)		2/1X
Wheel tread,load side	mm	1500
Fork Tilt front/rear	°	1/5
Mast closed height	mm	4329
Free lift height	mm	3366
Lift height	mm	10000
Mast extended height with load-backrest	mm	10964
Overhead guard height	mm	2245
Seat height	mm	1186
First stage height	mm	390
Leg height	mm	453
Overall length	mm	2384
Length from tail to fork face	mm	1464
Overall width	mm	1790/1270
Fork size	l/e/s(mm)	920×100×45
Load backrest height	mm	2360
Fork outside width	mm	400-2300
Inner leg width	mm	977
Reach distance	mm	740
Mast clearance	mm	75
Side driving aisle width(pallet1000x1000)	Ast(mm)	2665
Turning radius	Wa(mm)	1987
Driving speed(load/unload)	km/h	8.5/10
Lifting speed(load/unload)	mm/s	260/330
Lowering speed(load/unload)	mm/s	300/250
Max gradeability load/unload(S2-5min)	%	≤10
Brake type		Electromagnetic type
Driving motor(S2-60min)	kw	8
Lifting motor(S3-15%)	kw	15
Battery voltage/capacity	V/Ah	48/560
Battery weight	kg	921